

IOVU-430M

ARM-based Panel PC


While touch sensor is commonplace for single points of contact, IOVU-430M's multi-touch sensor enables a user to interact with the system with more than one finger at a time. IOVU-430's RISC-based system provides high performance, lower power consumption, wide operating temperature, rugged compact form factor and cost-effective. Built-in WiFi module, GPIO (general purpose input/output) and CAN bus control have varied applications be flexible.



Whole plane multi-touch panel PC

Features:

- RISC-based processor provides high performance and extremely low power consumption
- 4.3" widescreen WQVGA TFT LCD with projected-capacitor touch screen
- Multi-touch function provides flexible touch control
- Compact design with plastic housing and fan-less system
- Built-in 1.5w speakers
- Built-in 802.11b/g WiFi function
- CAN bus and GPIO provide flexible industrial control
- The whole plane multi-touch screen and IP65 compliant
- Mini secure digital card slot for storage extension



Application




IOVU-430M Specifications

Model	IOVU-430M
LCD size	4.3"
Max. Resolution	480 x 272
Brightness (cd/m²)	400
LCD Color	262K
Pixel Pitch (mm)	0.066(H) x 0.198(V)
Backlight MTBF	10000 hrs
Touch Screen	Projected-Capacitor
CPU	MARVELL XScale PXA270 416MHz
RAM	128MB SDRAM
Bootloader Storage	2MB boot ROM
OS/Program Storage	1GB Mini Secure Digital card
I/O Ports and Switches	1 x RS-232/422/485 COM port (software controllable) 1 x Reset button 1 x 10/100Mbps LAN 1 x USB1.1 host 1set CAN bus 6sets GPIO 2pin Terminal block DC input

Audio	1.5W speaker x 2
Construction Material	ABS + PC Plastic
LED Function	1 x Power ON/OFF LED on front panel
Mounting	Wall, Stand, Vstand and Arm (VESA 50 x 50)
Front Panel Color	Black
Dimension (W x H x D mm)	145 x 104 x 34
Operation Temperature (°C)	-20°C ~ 60°C
Storage Temperature (°C)	-20°C ~ 80°C
Net Weight (kg)	0.7
IP Level (front panel)	IP 65
Power Requirement	12~36V DC input
Power Consumption	7W

Dimensions (Unit : mm)



Packing List

- 1 x IOVU-430M
- 1 x Null modem cable
- 1 x Screw kits
- 1 x Utility CD includes SDK, utilities, and technical document
- 1 x Touch pen

Ordering Information

Part No.	Description
IOVU-430M-CE5/-R10	4.3" TFT, WQVGA, 262K color, Multi-touch Panel PC with built-in Windows® CE 5.0 license

Options

Part No.	Description
63000-UP0451E24P56L-RS	24V DC 45W power adapter with bare wire 90~264V AC input