

PoE+ PD Module

DC-PD



Features

- IEEE802.3at/af compliant
- PoE+ Powered Device (PD) with an isolated power supply using synchronous Flyback topology
- DC Output max power for 5V / 7A, 12V / 6A

Product Description

| | |
|------------------|---|
| Interface | RJ45 for connecting with PSE Internal 12-pin head for connecting with MPX-350 or MPX-210D Internal 2-pin terminal block for DC input of powered board |
| Cable | OALPOE-02 and OALPOE-03 for MPX-350 or MPX-210D OALDC-DC3 for DC output (please refer manual for the details) |
| Dimension | 84.05mm x 40.00mm |

Operating Conditions

| | |
|-------------------------------|--|
| Power Requirement | T series DC Input voltages from 37V to 57V R series from Power Sourcing Equipment |
| Controller Temperature | -40~+85°C |

Ordering Information

| | | |
|----------------------------------|------------------------|--|
| Art. No. 15(&\$- | DC-PD-5VT : | Compliant IEEE802.3at/af, with Terminal Block, DC Output 5V / 7A |
| Art. No. 15(&)%\$ | DC-PD-5VR : | Compliant IEEE802.3at/af, with RJ45 connector, DC Output 5V / 7A |
| Art. No. 15(&)%& | DC-PD-5VR-02 : | Compliant IEEE802.3at/af, with RJ45 connector, with miniPCle MPX-350 , DC Output 5V / 7A |
| Art. No. 15(&)%& | DC-PD-5VR-03 : | Compliant IEEE802.3at/af, with RJ45 connector, with miniPCle MPX-210D , DC Output 5V / 7A |
| Art. No. 15(&)% | DC-PD-12VT : | Compliant IEEE802.3at/af, with Terminal Block, DC Output 12V / 6A |
| Art. No. 15(&)%< | DC-PD-12VR : | Compliant IEEE802.3at/af, with RJ45 connector, DC Output 12V / 6A |
| Art. No. 15(&)%< | DC-PD-12VR-02 : | Compliant IEEE802.3at/af, with RJ45 connector, with miniPCle MPX-350 , DC Output 12V / 6A |
| Art. No. 15(&)%< | DC-PD-12VR-03 : | Compliant IEEE802.3at/af, with RJ45 connector, with miniPCle MPX-210D , DC Output 12V / 6A |